

iLED-FM0.7COB-GA

Vistrol Gaia Series COB LED Fine Pitch Display Panel

The iLED-FM0.7COB-GA features cutting-edge COB (Chip-on-Board) technology offering the best in image quality, durability, and versatility.

Features

- Visual Brilliance**
COB LED displays redefine visual excellence. By integrating LED chips directly on the board, they deliver unmatched image quality and clarity, ensuring your content shines brilliantly.
- Seamless Design**
Say goodbye to bezels and gaps. COB technology enables ultra-compact, borderless displays, providing a more immersive viewing experience.
- Exceptional Durability**
Built to last, COB LED displays are robust and reliable.
- Energy Efficiency**
Enjoy energy savings without compromising on brightness. COB displays are highly efficient, reducing power consumption while maintaining vivid visuals.
- Versatile Applications**
From the control room to the meeting room, COB LED displays find their place everywhere. Their flexibility in size, shape, and resolution makes them suitable for various industries and purposes.



✓ Technical Specifications

LED MODULE	
Model Number	iLED-FM0.7COB-GA
Pixel Pitch (mm)	0.78
LED Type	COB 1R1G1B (Flip Chip)
Module Size (mm)	150 x 168.75 mm
Module Pixel Density	192 x 216 dots
Module Weight (kg)	0.15kg
LED PANEL	
Cabinet Size WxHxD(mm)	600 x 337.5 x 37 mm
Pixel Density	768 x 432 dots
Material	Die casting aluminum
Cabinet Weight (kg)	4.6kg
Viewing Angle H°/V°	170°/160°
Drive Type	1/64
PHOTOELECTRONIC PARAMETERS	
Brightness (nits)	600 nits
Greyscale (bits)	13 bits
Refresh Rate (hz)	3840 hz
Color Temperature (K)	3200~9300 K
Contrast Ratio	1:10,000

APPLICATION	
AC Operating Voltage	100~240 V
AC Input Frequency	50/ 60 Hz
Power Consumption (Max.)	320 W/m ²
MTBF	>100,000hrs
Storage Temperature (°C)	-20~+65 °C
Operating Temperature(°C)	-10~+45 °C
Storage Humidity (RH)	10%~90%
Operating Humidity (RH)	10%~90%
IP Rating (Front)	IP65 / IP30
Panel Maintenance Type	Front Maintenance
Panel Installation Type	Front Installation
Redundant Power Supply	Optional
Certificate	CE, FCC

Vistrol
Singapore | Malaysia
w www.vistrol.com
e sales@vistrol.com

ISO 9001:2005 Certified Company:



* For any enquiry , please send email to sales@vistrol.com