



iLED-FF1.2COB-GA

Vistrol Gaia Series COB LED Fine Pitch Display Panel

The iLED-FF1.2COB-GA features cutting-edge COB (Chip-on-Board) technology offering the best in image quality, durability, and versatility.

Features


- **Visual Brilliance**
COB LED displays redefine visual excellence. By integrating LED chips directly on the board, they deliver unmatched image quality and clarity, ensuring your content shines brilliantly.
- **Seamless Design**
Say goodbye to bezels and gaps. COB technology enables ultra-compact, borderless displays, providing a more immersive viewing experience.
- **Exceptional Durability**
Built to last, COB LED displays are robust and reliable.
- **Energy Efficiency**
Enjoy energy savings without compromising on brightness. COB displays are highly efficient, reducing power consumption while maintaining vivid visuals.
- **Versatile Applications**
From the control room to the meeting room, COB LED displays find their place everywhere. Their flexibility in size, shape, and resolution makes them suitable for various industries and purposes.

**✓ Flip Chip**

- **No Wire Bonding**
- **High Contrast Ratio**
- **Blacker and Better Display Effect**

✓ Anti Collision and Easy Cleaning

Vistrol COB
After Collision Test
(>10kg, ~1m Height)



SMD
After Collision Test
(>10kg, ~1m Height)




Easy to Clean with Water

✓Extremely Low Pixel Failure Rate



Vistrol COB
(<10PPM)



SMD
(>50PPM)

✓Technical Specifications

LED MODULE	
Model Number	iLED-FF1.2COB-GA
Pixel Pitch (mm)	1.26
LED Type	COB
Module Size (mm)	304 x 342mm
Module Pixel Density	240 x 270dots
Module Weight (kg)	1.1kg
Color Temperature (K)	3200~9300K
LED PANEL	
Cabinet Size WxHxD(mm)	608 x 342 x 36mm
Pixel Density	480 x 270dots
Material	Die casting aluminum
Cabinet Weight (kg)	5.2kg
Viewing Angle H°/V°	165°/145°
PHOTOELECTRONIC PARAMETERS	
Brightness (nit)	800 cd/m ²
Greyscale	13bits
Refresh Rate (hz)	3840hz
Color Temperature (K)	3200~9300K
APPLICATION	
AC Operating Voltage	100~240 V
AC Input Frequency	50/ 60 Hz
Power Consumption (Max.)	200 W/m ²
Storage Temperature (°C)	-20~+60 °C
Operating Temperature(°C)	-10~+40 °C
Storage Humidity (RH)	10%~90%
Operating Humidity (RH)	10%~90%
Panel Maintenance Type	Fully front
Panel Installation Type	Front Installation
Redundant Power Supply	Optional
Certificate	CE, RoHS, FCC

Vistrol

Singapore | Malaysia

w www.vistrol.com
e sales@vistrol.com

ISO 9001:2005 Certified Company:



* For any enquiry , please send email to sales@vistrol.com

R01-V1.9